

3 - 5 February, 2025

RIYADH INTL. CONVENTION & EXHIBITION
CENTER, SAUDI ARABIA



Saudi
International
Marine
Exhibition
EQUIPMENT
BROCHURE '25

We Are Lowe.

Lowe is a global, innovative, ambitious and award-winning refrigeration equipment company. Established in 1977, Lowe has grown to be the largest globally recognised refrigeration equipment company for the retail, exhibitions and events markets.



Service

Low Rental have unrivaled experience in the local and the global F&B, retail, events and exhibitions market. Tailored advice for refrigeration equipment selection with a top range of equipment, selection of high-impact equipment, and Fully managed installation on-site with servicing and support through the rental period.



The High Impact Refrigeration Selection – Grab n’go



CT SERIES

Multi-Deck Display Fridge

Model	C2T	C3T
Dimensions (W×D×H) mm	1330×870×2070	1955×870×2030
Display Area (m ²)	1.88	2.9
Electrical Req. (Watts)	2028	2403
Temperature Range	+1...+4°C	+1...+4°C



C1T

Multi-Deck Display Fridge

Model	C1T
Dimensions (W×D×H) mm	1038×870×2070
Display Area (m ²)	1.41
Electrical Req. (Watts)	1653
Temperature Range	+1...+4°C

Display Chillers/Freezer

Refrigeration Selection – With Door



K1
Dual Temperature Display Freezer

Model	K1
Dimensions (W×D×H) mm	600×600×1800
Volume (L)	400
Electrical Req. (Watts)	1057
Temperature Range	+5...-18°C



K1R
Dual Temp Display Chiller/Freezer

Model	K1R
Dimensions (W×D×H) mm	600×600×1800
Volume (L)	350
Electrical Req. (Watts)	500
Temperature Range	-18...+5°C



G4
Glass Door Chiller

Model	G4
Dimensions (W×D×H) mm	610×620×1885
Volume (L)	382
Electrical Req. (Watts)	460
Temperature Range	+1...+10°C



G7XXL
Dual Temp Double Glass Door Freezer / Chiller

Model	G7XXL
Dimensions (W×D×H) mm	1320×890×1930
Volume (L)	1270
Electrical Req. (Watts)	1400
Temperature Range	-21...+5°C



G7DC
Double Glass Door Chiller

Model	G7DC
Dimensions (W×D×H) mm	1250×686×2025
Volume (L)	1000
Electrical Req. (Watts)	619
Temperature Range	+1...+4°C

Display Chillers

Refrigeration Selection



A SERIES

Serve-Over Counter

Model	A1P	A2P	A3P	GF-A1P	GF-A2P
Dimensions (WxDxH) mm	1290x955x1270	1890x955x1270	2485x955x1270	1040x900x1265	1520x900x1265
Volume (L)	286	429	572	45	90
Electrical Req. (Watts)	648	960	1296	430	470
Temperature Range	-1 - +7°C	-1 - +7°C	-1 - +7°C	+2 - +5°C	+2 - +5°C



A1C

Serve-Over Display Counter

Model	A1C	A2C
Dimensions (WxDxH) mm	1280x975x1285	1800x975x1285
Volume (L)	387	580
Electrical Req. (Watts)	750	1000
Temperature Range	0...+5°C	0...+5°C



L1A

1.2m Curved Glass Patisserie Case

Model	L1A
Dimensions (WxDxH) mm	1200x1200x840
Volume (L)	360
Electrical Req. (Watts)	1000
Temperature Range	+2°C ~ +10°C



H3DD

2 Door Front Venting Back Bar Chiller

Model	H3DD
Dimensions (WxDxH) mm	905x520x900
Volume (L)	200
Electrical Req. (Running Watts)	1081
Temperature Range	+2°C ~ +10°C



GF-L1S

Rectangular Confectionery Showcase (2 Tier)

Model	GF-L1S
Dimensions (WxDxH) mm	900x700x1350
Volume (L)	316
Electrical Req. (Running Watts)	685.6 - 704.0
Temperature Range	+1 to +6°C



The Display Freezer Collection



D1C

1.5m Curved Glass Display Freezer

Model	D1C
Dimensions (WxDxH) mm	1473x760x865
Volume (L)	500
Electrical Requirements (Watts)	672
Temperature Range	-25...+10°C

The Display Freezer Collection

Glass Doors



GF-G1

Glass Door Freezer

Model	GF-G1
Dimensions (WxDxH) mm	670x718x2026
Volume (L)	450
Electrical Requirements (Watts)	-
Temperature Range	-



G7DF

Dual Temp Double Glass Door Freezer / Chiller

Model	G7DF
Dimensions (WxDxH) mm	1250x686x2025
Volume (L)	1000
Electrical Requirements (Watts)	789
Temperature Range	-18...-20°C

Advanced Storage Chillers & Freezers



GN1DUC

Single Door Upright Chiller

Model	GN1DUC
Dimensions (W×D×H) mm	670×800×1990
Volume (L)	420
Electrical Req. (Watts)	300
Temperature Range	-2 to +8°C



GN1DUF

Single Door Upright Freezer

Model	GN1DUF
Dimensions (W×D×H) mm	670×800×1990
Volume (L)	420
Electrical Req. (Watts)	300
Temperature Range	-18...-22°C



GN3DBC

3 Door Bench Chiller

Model	GN3DBC
Dimensions (W×D×H) mm	1750×700×850
Volume (L)	428
Electrical Req. (Watts)	330
Temperature Range	0...18°C

Advanced Storage Chillers & Freezers



GF- E1AA

Sliding Door Freezer

Model	GF- E1AA
Dimensions (WxDxH) mm	598x1054x825
Volume (L)	258
Electrical Req. (Watts)	-
Temperature Range	-



BLAST

204Ltr Slim Blast Chiller / Freezer

Model	Blast
Dimensions (WxDxH) mm	500x700x2040
Volume (L)	204
Electrical Req. (Watts)	975
Temperature Range	-18 to -20 / 0 to +4°C



E1NL

High Vision Display Freezer

Model	E1NL
Dimensions (WxDxH) mm	1540x910x1000
Volume (L)	556
Electrical Req. (Watts)	1104
Temperature Range	-18...-23°C



H2

71L Storage Freezer

Model	H2
Dimensions (WxDxH) mm	494x494x847
Volume (L)	71
Electrical Req. (Watts)	120
Temperature Range	-18...-22°C

High Impact Catering Range Ovens & Microwaves Selection



TURBOFAN 4 TRAY CONVECTION OVEN

Compatibility GN1/1
Temperature 50 - 260°C

Model	H17C
Dimensions (WxDxH) mm	810×660×1510
El. Consumption (W)	3.1



750W COMMERCIAL MICROWAVE

240V
Single Phase/Neutral

Model	H12A
Dimensions (WxDxH) mm	500×400×300
El. Consumption (W)	1.5

High Impact Catering Range

Flat Griddle



ELECTRIC TABLE TOP FLAT GRIDDLE

32 Amp Blue C-Form Socket

Model H9A
Dimensions (W×D×H) mm: 750×465×240
Temperature: 50-240°C



ELECTRIC TABLE TOP FLAT GRIDDLE – SMALL

Temperature range 50-240°C

Model H9E
Dimensions (W×D×H) mm: 550×465×240
El. Consumption (kW): 2.9



FLAT GRIDDLE

Cooking Area (W×D) mm 780×490

Model H91A
Dimensions (W×D×H) mm: 800×770×890
El. Consumption (kW): 6.9

Hight Impact Catering Range



SINGLE INDUCTION HOTPLATE

260mm ring diameter

Model H10A
Dimensions (WxDxH) mm: 330x430x100
El. Consumption (kW): 3



DOUBLE INDUCTION HOTPLATE

240V/Single Phase/Neutral

Model H10B
Dimensions (WxDxH) mm: 650x370x70
El. Consumption (kW): 3



PASTA COOKER

400V/Three Phase/Neutral

Model H29B
Dimensions (WxDxH) mm: 400x730x850
Temperature: 70 - 100°C



TABLE TOP SHAWARMA MACHINE

32 Amp Red C-Form Socket

Model H66
Dimensions (WxDxH) mm: 535x610x1000
El. Consumption (kW): 9.9



TABLE TOP FRYER

5 ltr. oil capacity

Model H15A
Dimensions (WxDxH) mm: 270x400x300
El. Consumption (kW): 2.8



FULL HEIGHT DEEP FRYER FLOOR STANDING

28 ltr. oil capacity

Model H15E
Dimensions (WxDxH) mm: 400x800x1110
El. Consumption (kW): 16-18



Cooking Essentials

Cooking Essentials



WATER DISPENSOR

19 ltr. bottle capacity

Model H7
Dimensions (WxDxH) mm: 300×330×1400
El. Consumption (kW) 0.6



STICK BLENDER

4 blade emulsifying knife

Model H43B
Dimensions (dia.×H) mm: 70×395
El. Consumption (kW): 0.22



PLANETARY MIXER

4 ltr. capacity

Model H44B
Dimensions (WxDxH) mm: 230×400×300
El. Consumption (kW) 1.4

Cooking Essentials



0.7M STAINLESS STEEL TABLE

Model H20A
Dimensions (WxDxH) mm: 700x600x900
Stainless Steel Undershelf



DOUBLE BOWL STAINLESS STEEL SINK

Hot Water Connection

Model H21B
Dimensions (WxDxH) mm: 1500x600x900
Water Inlet / Drain: In 1/2" BSP - Out 40mm diam



2.1M SELF-STANDING EXTRACTOR HOOD

For electric equipment use only

Model EH21D
Dimensions (WxDxH) mm: 2100x1000x2500
El. Consumption (kW): 1



GLASS/DISHWASHER 50X50

Model H47B
Dimensions (WxDxH) mm: 580x610x830
Electrical Consumption (kW): 2

Care Maintenance

Low Rental supply all equipment with delivery, installation, maintenance, and dismantling. No maintenance bills for equipment failures - ever. Your payment includes all the costs of maintenance. We don't do hidden charges.





+44 (0) 28 9260 4619

@ info@lowerental.com

www.lowerental.com/sa-en/